





**\* INDICATES APPLICABILITY OF A SPECIFIC CONTROL MEASURE TO ONE OR MORE OF THE SEVEN PROBLEM AREAS.**

SLOPES	A	B	C	D	E	F	G
STREAMS AND WATERWAYS	*	*	*				
SURFACE DRAINAGE							
ENCLOSED DRAINAGE (INLET & OUTFALL CONTROL)							
LARGE FLAT SURFACE AREAS					*		
BORROW AND STOCKPILE AREAS						F	
ADJACENT PROPERTIES							G

37		WEIR	CONTROLS SEDIMENTATION IN LARGE STREAMS. CAUSES MINIMAL TURBIDITY.
38		RETAINING WALL	REDUCES GRADIENT WHERE SLOPES ARE EXTREMELY STEEP. PERMITS RETENTION OF EXISTING VEGETATION, KEEPS SOIL STABLE IN CRITICAL AREAS. MINIMIZES MAINTENANCE.
39		SEEPAGE CONTROL	PREVENTS PIPING AND SOIL SLIPPAGE ON CUT SLOPES.
40		WINDBREAK	MINIMIZES WIND EROSION. MAY BE SNOW FENCE.

C					
B					
A					
DESCRIPTION	DRW	CKD	APP	DATE	
REVISIONS					
DRAWN BY: S.D.A.					
CHECKED BY: S.D.A.					
APPROVED:					

**SOIL EROSION  
AND SEDIMENTATION  
CONTROL MEASURES  
(FROM 37-40)**

SCALE: NONE

CITY OF DETROIT  
WATER AND SEWERAGE  
DEPARTMENT  
ENGINEERING  
DIVISION

SHEET 9 OF 9

DWG No. 01014-17