

STANDARD SPECIFICATIONS

REFERENCE: UL 83, ICEA S-95-658 (NEMA WC 70).
 CONDUCTOR: Solid, uncoated copper. Maximum operating temperature 90°C dry, 75°C wet.
 INSULATION: Polyvinyl chloride, UL 83, Type THHN and THWN, ICEA S-95-658.
 SHIELD: None.
 JACKET: Conductor: Nylon, 4 mils (100 µm) minimum thickness, UL 83.
 FACTORY TESTS: Cable shall meet the requirements of UL 83 for Type THHN and THWN.

Cable Details

Size		Number of Strands	Conductor Insulation Thickness *		Maximum Outside Diameter	
AWG or mcm	mm ²		in.	µm	in.	mm
12	4.0	1	0.015	380	0.17	4.32
10	6.0	1	0.020	510	0.20	5.08

*The average thickness shall be not less than that indicated above. The minimum thickness shall not be less than 90 percent of the values indicated above.

A durable marking shall be provided on the surface of the cable at intervals not exceeding 24 inches (600 mm). Marking shall include manufacturer's name, THWN or THHN, conductor size, and 600 volt.

C						600 Volt, Single Conductor Lighting Cable (600-1-PVC-THHN-THWN)	CITY OF DETROIT WATER AND SEWERAGE DEPARTMENT ENGINEERING DIVISION	
B								
A								
	DESCRIPTION	DRW	CKD	APP	DATE			
REVISIONS								
DRAWN BY: B & V								SHEET 1 OF 1
CHECKED BY: S.D.A.								DWG No. 16050-1
APPROVED:							SCALE: NONE	